

Re: [fw-wiz] Real Traffic Testing

Source: <http://www.derkeiler.com/Mailing-Lists/Firewall-Wizards/2003-10/0164.html>

From: John Adams (jna_at_retina.net)

Date: 10/24/03

To: Gianpiero Porchia <gianpiero.porchia@atsweb.it>

Date: Fri, 24 Oct 2003 14:47:39 -0700 (PDT)

- > - *Get traffic from OUTSIDE to INSIDE using TAP-1*
- > - *Get traffic from INSIDE to OUTSIDE using TAP-2*

This looks like asymmetric routing to me, and I don't see how you're going to make this work.

Are these stateful firewalls? How are the two firewalls going to share the state table for inbound/outbound packets and handle them correctly?

> *The problems:*

- > - *The traffic is directed to the MAC address of FW, so FW-test will drop it;*

Well, the packets are rewritten by your outside router on the way in, and the router isn't going to know which firewall handled the transaction.

> *Have you some idea to get the objectives?*

You can't make this work unless the firewalls are in some sort of active, redundant configuration, with exactly the same configurations and shared state tables.

-john

--

J. Adams <http://www.retina.net/~jna>

firewall-wizards mailing list
firewall-wizards@honor.icsalabs.com
<http://honor.icsalabs.com/mailman/listinfo/firewall-wizards>