

Re: Openssh and sendmail signatures

Source: <http://www.derkeiler.com/Mailing-Lists/securityfocus/focus-linux/2002-09/0004.html>

From: Johannes Ullrich (jullrich@euclidian.com)

Date: 09/11/02

Date: Wed, 11 Sep 2002 12:13:15 -0400
From: "Johannes Ullrich" <jullrich@euclidian.com>
To: monz@danbbs.dk

> *How do I prevent Openssh telling which version is running?*
> *Likewise with sendmail? (I know you'll tell med to use another MTA..).*

openssh: you need to patch the source afaik. no simple solution.

sendmail: in sendmail.cf, look for:
SMTP initial login message (old \$e macro)
O SmtgGreetingMessage=\$j Sendmail \$v/\$Z; \$b

\$j – hostname (see line that starts with 'Dj')
\$Z – version (see line that starts with 'DZ')
\$b – time

Its recommended to keep \$j , in order to identify the name servers
host name. other then that, just change it...

O SmtgGreetingMessage=\$j My_Supermailer – Do not relay.

--

jullrich@euclidian.com

Collaborative Intrusion Detection
join <http://www.dshield.org>

- application/pgp-signature attachment: stored
-

- **Previous message:** Dr. Michael G. Mathews: "Re: Openssh and sendmail signatures"
- **In reply to:** Mogens Valentin: "Openssh and sendmail signatures"
- **Next in thread:** Robert W. Jaroszuk: "Re: Openssh and sendmail signatures"
- **Messages sorted by:** [date] [thread] [subject] [author] [attachment]