

## Pentesting Cisco 3640 devices via dialup ?

*Source:* <http://www.derkeiler.com/Mailing-Lists/securityfocus/pen-test/2002-07/0133.html>

---

*From:* [r00t@online.ie](mailto:r00t@online.ie)

*Date:* 07/30/02

From: <[r00t@online.ie](mailto:r00t@online.ie)>  
Date: Tue, 30 Jul 2002 13:36:07 +0100  
To: [pen-test@securityfocus.com](mailto:pen-test@securityfocus.com)

Hi all,

Sorry to bother you with this quite basic question. I am pretty new to pen-testing Remote Access servers.

I am due to start a massive pen-testing project in two weeks, a small part of the project requires pen-testing of Cisco 3640 devices over dialup.

I am looking for some assistance in how to brute force usernames / passwords over dialup.

From what I know so far, by default Cisco devices will disconnect a user from a dialup session after 3 unsuccessful authentication attempts, which means I need to manually re-initiate the dialup connection every 50-60 seconds. I feel this will be infeasible due to the time required to crack a single password.

Could anyone suggest a way to automate this. Or could anyone who has pen-tested RAS servers over dialup specify an alternative method.

Any help whatsoever is very much appreciated.

Thanks in advance

./Mark

---

This list is provided by the SecurityFocus Security Intelligence Alert (SIA) Service. For more information on SecurityFocus' SIA service which automatically alerts you to the latest security vulnerabilities please see: <https://alerts.securityfocus.com/>

---

- *Previous message:* [Daniel Polombo: "RE: SQL Injection Legalities"](#)
- *Next in thread:* [Zen: "Re: Pentesting Cisco 3640 devices via dialup ?"](#)
- *Reply:* [Zen: "Re: Pentesting Cisco 3640 devices via dialup ?"](#)
- *Messages sorted by:* [\[ date \]](#) [\[ thread \]](#) [\[ subject \]](#) [\[ author \]](#) [\[ attachment \]](#)