

ipchains and ntp udp port 123

Source: <http://www.derkeiler.com/Newsgroups/comp.os.linux.security/2002-06/0706.html>

From: Robert Lomitola (ralnw6@bellsouth.net)

Date: 06/17/02

From: Robert Lomitola <ralnw6@bellsouth.net>

Date: Mon, 17 Jun 2002 16:13:16 -0400

I have a redhat72 machine used as a gateway that I am trying to get ntpd to work. The message log shows the firewall deny the packets from time.nist.gov at 192.43.244.18:123 on the ppp0 interface. i have tried ipchains -A input -p udp -i ppp0 -s 192.43.244.0/24 123 -j ACCEPT

Then I did a ipchains-save >/home/xyz/ipchains.rules

I then inserted this line

```
-A input -s 192.43.244.0/255.255.255.0 123:123 -d 0.0.0.0/0.0.0.0 -i ppp0 -p 17 -j ACCEPT
```

into the /etc/sysconfig/ipchains file above this line

```
-A input -s 0/0 -d 0/0 -p udp -j REJECT
```

I also tried directly editing the ipchains file with

```
-A input -s 192.43.244.18 123 -d 0/0 -p udp -j ACCEPT
```

If I turn off the ipchains service briefly I can successfully run ntpdate time.nist.gov and I sync up with the time server otherwise it doesn't work. High security option was selected during the installation and the server is patched up to date.

Best regards,

- **Next message:** [Kasper Dupont: "Re: Preventing uploads on a specific port to internet."](#)
- **Previous message:** [www.e-portfolio.co.yu: "----- BERZA IT POSLOVA -----"](#)
- **Messages sorted by:** [\[date \]](#) [\[thread \]](#) [\[subject \]](#) [\[author \]](#) [\[attachment \]](#)